

Extra Clear



Constructie | Composition | Konstruktion | Construction

Buitenblad	4T - Extra helder
Exterieur	4T- Extra clair
Außen	4T - Extra hell
Outer pane	4T - Extra Clear
Verdeler	0,3 Vacuüm
SZR	0,3 Vakuum
Intercalaire	0,3 Sous-vide
Spacer	0,3 vacuum
Binnenblad	4T - Extra helder
Intérieur	4T- Extra clair
Innen	4T - Extra hell
Inner Pane	4T - Extra Clear

Specificaties | Spécifications | Spezifikationen | Specifications

	LTA	83	Lichttransmissie
	TL		Transmission Lumineuse
	LT		Lichttransmission
	LT		Light transmission
EN410:2011	BLR	0,15	Buiten lichtreflectie
	RLE		Réflexion Lumineuse Extérieure
	Lra		Lichtreflexion außen
	ELR		External light reflection
	LR (binnen)	0,16	Binnen lichtreflectie
	RLI		Réflexion lumineuse Intérieure
	Lri		Lichtreflexion innen
	ILR		Internal light reflection
	G-waarde	0,68	Zontoetredingsfactor
	Valeur G		Facteur Solaire
	G-wert		Gesamtenergiedurchlassgrad
	G-value		Solar factor
EN 674	U-waarde	0,50*	Isolatiewaarde
	Valeur U		Valeur d'isolation
	U-Wert		Dämmwert
	U-value		Insulation value
EN ISO 10140-1 / 2 EN ISO 717-1	RW (C ; Ctr) dB	36 (-2;-3)	Geluidsdemping
			Réduction du bruit
			Lärmminderung
			Sound insulation

*U-waarde gebaseerd op EN 674:2011 en ISO 19916-1:2018 (ift rosenheim, 2025).

* Valeur U basée sur EN 674:2011 et ISO 19916-1:2018 (ift Rosenheim, 2025).

*U-value based on EN 674:2011 and ISO 19916-1:2018 (ift Rosenheim, 2025).

* U-Wert basierend auf EN 674:2011 und ISO 19916-1:2018 (ift Rosenheim, 2025).



Netherlands

www.bengglas.nl
info@bengproducts.nl
+31 (0) 13 534 22 26

Belgium

www.bengglas.be
info@bengproducts.be
+32 (0) 19 60 08 31

